

FireWeave X is a narrow woven, high visibility, inherently flame resistant trim laminated with 3M™ Scotchlite™ 9740 Silver Reflective FR Industrial wash heat transfer film. Certified to all relevant standards, it offers a superior value to similar products, while maintaining exceptional performance in laundering and FR properties.



Standard Width - 2" (51mm)
Standard Roll Size - 109.4 yds (100m)

3M Industrial Wash Guidelines

Wash Chemistry	No detergents containing free sodium hydroxide or potassium hydroxide
Max. Wash Temperature	75°C (165°F)
Break/Suds Cycles	Less than 15 min. total
Tunnel Dry (Max inlet temp.)	120°C (250°F)
Tumble Dry (Max. exhaust temp.)	90°C (195°F)
Pressing (do not exceed)	150°C (300°F)

Certifications

Flame Resistance:
CAN/CGSB 155.20-2000 and 155.22-2014
UL Certified NFPA 2112-2012

High Visibility:
CSA Z96-09

AUTHORIZED CONVERTER
AND DISTRIBUTOR
3M Scotchlite™
Reflective Material
Matériau réfléchissant



3M™ Scotchlite™ 9740 Silver Reflective FR Industrial Wash Heat Transfer Film

Measured by 3M on new product at +5.0° entrance and 0.2° observation angles	500
---	-----

3M™ Scotchlite™ Industrial Wash Flame Resistant Heat Transfer Film

Inherently Flame Resistant High Visibility Tape



ALL GUIDELINES AND TECHNICAL INFORMATION ARE BASED ON WHAT WE BELIEVE TO BE ACCURATE. HOWEVER WE CANNOT GUARANTEE PERFORMANCE OF THE PRODUCT NOT UNDER THE MANUFACTURER'S CONTROL. PLEASE DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS END USE. THE USER ASSUMES ALL RISK AND LIABILITY WITH RESPECT TO THE USE OF THIS PRODUCT. WE WILL ONLY REPLACE GOODS DETERMINED BY THE SELLER AND MANUFACTURER AS DEFECTIVE.



**Block Bindings
& Interlinings Ltd**

9500 Rue Meilleur, Suite 402
Montreal, Quebec H2N 2B7
T. (514) 381-7493
F. (514) 381-6725