# PRO-EUT Glossy Heat Transfers

Pro-Cut Ultra Heat Transfers are created out of a durable, polyurethane based material, soft hand, highly flexible, glossy finish and scratch, crack, fade and UV resistant. These heat transfers out-perform screen-printing and can be dry cleaned. They are certified for no harmful substances, and are free from PVC, plasticizers, and heavy metals. Pro-Cut Ultra Heat Transfers allow you to create professional, personalized garments quickly, easily and cost-effectively. Available as transfers (no minimum purchase requirement) and roll good form (minimum purchase of 1 rolls - 15" x 5 yds).

### Application Instructions

**Heat Transfer Machine Settings:** 

Temperature: 300-330°F (155-165°C) Pressure: 60-80 PSI or 4-6 bar (Firm)

#### Step 1:

Preheat garment/panel 10-20 seconds prior to application of transfer.

#### Step 2:

Place heat transfer onto garment/panel. Cover with kraft or teflon paper. Using heat transfer settings, apply transfer for 15-20 seconds.

#### Step 3:

Let garment/panel cool down to room temperature. Remove heat transfer liner carefully.

### Recommended Fabrics:

100% Cotton 100% Polyester Poly/cotton Blends Polyester knits and mesh



### Care Instructions:

Machine wash using mild detergent.

Wash temperature should not exceed 140°F (60°C) Do not use bleach.

Dry at normal setting on household machines. Dry clean.

Do not commercial launder.

Do not iron directly onto heat transfer.

ALL GUIDELINES AND TECHNICAL INFORMATION ARE BASED ON WHAT WE BELIEVE TO BE ACCURATE. HOWEVER WE CANNOT GUARANTEE PERFORMANCE OF THE PRODUCT NOT UNDER THE MANUFACTURER'S CONTROL. PLEASE DETERMINE THE SUITABLITY OF THE PRODUCT FOR ITS END USE. THE USER ASSUMES ALL RISK AND LIABILITY WITH RESPECT TO THE USE OF THIS PRODUCT. WE WILL ONLY REPLACE GOODS DETERMINED BY THE SELLER AND MANUFACTURER AS DEFECTIVE.

Copyright © 2017




# Block Bindings & Interlinings Ltd

9500 Rue Meilleur, Suite 402 Montreal, Quebec H2N 2B7

T. (514) 381-7493 F. (514) 381-6725

# PRO-CUT Glossy Colour Guide





## Block Bindings & Interlinings Ltd

9500 Rue Meilleur, Suite 402 Montreal, Quebec H2N 2B7 T. (514) 381-7493 F. (514) 381-6725

<sup>\*\*\*</sup>Colours shown are approximate. The PANTONE information is for reference purposes.