

PRO-CUT Nylon Heat Transfers

Pro-Cut Nylon Heat Transfers are created out of a durable, polyurethane based material, soft hand, highly flexible, glossy finish and scratch, crack, fade and UV resistant. These heat transfers out-perform screen-printing and can be dry cleaned. They are certified for no harmful substances, and are free from PVC, plasticizers, and heavy metals. Pro-Cut Nylon Heat Transfers allow you to create professional, personalized garments quickly, easily and cost-effectively. Available as transfers (no minimum purchase requirement) and roll good form (minimum purchase of 1 rolls - 15" x 5 yds).

Application Instructions

Heat Transfer Machine Settings:

Temperature: 300-305°F (140-150°C)

Pressure: 60-80 PSI or 4-6 bar (Firm)

Step 1:

Preheat garment/panel 10-20 seconds prior to application of transfer.

Step 2:

Place heat transfer onto garment/panel. Cover with kraft or teflon paper. Using heat transfer settings, apply transfer for 4-5 seconds.

Step 3:

Let garment/panel cool down to room temperature. Remove heat transfer liner warm.

Step 4:

Cover with kraft or teflon paper. Using heat transfer settings, apply transfer for 10-15 seconds for final seal.

Recommended Fabrics:

Nylon
Textured silicone coated materials
Moisture-wicking materials
Shiny polyester

Care Instructions:

Machine wash using mild detergent.
Wash temperature should not exceed 105°F (40°C)
Do not use bleach.
Dry at normal setting on household machines.
Dry clean.
Do not commercial launder.
Do not iron directly onto heat transfer.

ALL GUIDELINES AND TECHNICAL INFORMATION ARE BASED ON WHAT WE BELIEVE TO BE ACCURATE. HOWEVER WE CANNOT GUARANTEE PERFORMANCE OF THE PRODUCT NOT UNDER THE MANUFACTURER'S CONTROL. PLEASE DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS END USE. THE USER ASSUMES ALL RISK AND LIABILITY WITH RESPECT TO THE USE OF THIS PRODUCT. WE WILL ONLY REPLACE GOODS DETERMINED BY THE SELLER AND MANUFACTURER AS DEFECTIVE.



Copyright © 2017

**Block Bindings
& Interlinings Ltd**

9500 Rue Meilleur, Suite 402
Montreal, Quebec H2N 2B7
T. (514) 381-7493
F. (514) 381-6725

PRO-CUT Nylon Colour Guide



WHITE



BLACK



LIGHT BLUE PMS 2925C



ROYAL BLUE PMS 647C



NAVY BLUE PMS 296C



YELLOW 1235C



GREEN PMS 349C



FOREST GREEN PMS 553C



PURPLE PMS 273C



GREY PMS 430C



ORANGE PMS 164C



RED PMS 187C



BORDEAUX PMS 216C



METALLIC SILVER PMS 877C



METALLIC GOLD 871C



**Block Bindings
& Interlinings Ltd**

9500 Rue Meilleur, Suite 402
Montreal, Quebec H2N 2B7

T. (514) 381-7493

F. (514) 381-6725

***Colours shown are approximate. The PANTONE information is for reference purposes.