

# PRO-CUT

## Heat Transfers

Pro-Cut Heat Transfers are created out of a durable, polyurethane based material, soft hand, highly flexible, matte finish and scratch, crack, fade and UV resistant. These heat transfers out-perform screen-printing and can be dry cleaned. They are certified for no harmful substances, and are free from PVC, plasticizers, and heavy metals. Pro-Cut Heat Transfers allow you to create professional, personalized garments quickly, easily and cost-effectively. Available as transfers (no minimum purchase requirement) and roll good form (minimum purchase of 1 rolls - 19.7" x 5 yds).

### Application Instructions

Heat Transfer Machine Settings:

Temperature: 300-330°F (155-165°C)

Pressure: 60-80 PSI or 4-6 bar (Firm)

#### **Step 1:**

Preheat garment/panel 10-15 seconds prior to application of transfer.

#### **Step 2:**

Place heat transfer onto garment/panel. Cover with kraft or teflon paper.  
Using heat transfer settings, apply transfer for 15-20 seconds.

#### **Step 3:**

Let garment/panel cool down to room temperature (warm). Remove heat transfer liner carefully.

### Recommended Fabrics:

100% Cotton

100% Polyester

Poly/cotton Blends

Polyester knits and mesh

### Care Instructions:

Machine wash using mild detergent.

Wash temperature should not exceed 140°F (60°C)

Do not use bleach.

Dry at normal setting on household machines.

Dry clean.

Do not commercial launder.

Do not iron directly onto heat transfer.



ALL GUIDELINES AND TECHNICAL INFORMATION ARE BASED ON WHAT WE BELIEVE TO BE ACCURATE. HOWEVER WE CANNOT GUARANTEE PERFORMANCE OF THE PRODUCT NOT UNDER THE MANUFACTURER'S CONTROL. PLEASE DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS END USE. THE USER ASSUMES ALL RISK AND LIABILITY WITH RESPECT TO THE USE OF THIS PRODUCT. WE WILL ONLY REPLACE GOODS DETERMINED BY THE SELLER AND MANUFACTURER AS DEFECTIVE.

Copyright © 2014



**Block Bindings  
& Interlinings Ltd**

9500 Rue Meilleur, Suite 402  
Montreal, Quebec H2N 2B7

T. (514) 381-7493

F. (514) 381-6725

# PRO-CUT Colour Guide



WHITE



BLACK



CRIMSON PMS 201C



RED PMS 187C



FLAME RED PMS 032C



LEMON YELLOW PMS 3955C



MEDIUM YELLOW 123C



YELLOW 1235C



APPLE GREEN PMS 375C



LIGHT GREEN PMS 366C




GREEN PMS 349C



FORREST GREEN PMS 553C



OLIVE DRAB PMS 581C



AQUA PMS 2572C



LIGHT BLUE PMS 2925C



SKY BLUE PMS 2915C



ICE BLUE PMS 291C



SAPPHIRE PMS 285C



ROYAL BLUE PMS 647C



NAVY BLUE PMS 296C



TURQUOISE PMS 3155C



BABY PINK 189C



MAGENTA PMS 210C



FUSCHIA PMS 215C



VIOLET PMS 665C



PURPLE PMS 273C



LILAC PMS 2572C



TEXAS ORANGE PMS 581C



ORANGE PMS 164C



TANGERINE PMS 581C



BORDEAUX PMS 216C



OCHRE PMS 1245C



BROWN PMS 4625C



BEIGE PMS 7401C



GREY PMS 430C



WINE 7420C



NEON YELLOW PMS 809C



NEON GREEN PMS 802C



NEON PINK PMS 806C



NEON ORANGE 805C



VEGAS GOLD 7502C



METALLIC GOLD 871C



METALLIC SILVER PMS 877C

\*\*\*Colours shown are approximate. The PANTONE information is for reference purposes.



**Block Bindings  
& Interlinings Ltd**

9500 Rue Meilleur, Suite 402  
Montreal, Quebec H2N 2B7

T. (514) 381-7493

F. (514) 381-6725