

PRO-PRINT (Nylon) Heat Transfers

Pro-Print (Nylon) Heat Transfers are created out of a durable, polyurethane based material a special adhesive for hydrophobic and impregnated nylon textiles. It has a soft hand, highly flexible, matte finish and scratch, crack, fade and UV resistant. These heat transfers out-perform screen-printing. They are certified for no harmful substances, and are free from PVC, plasticizers, and heavy metals. Pro-Print (Nylon) Heat Transfers allow you to create professional, personalized garments quickly, easily and cost-effectively. Available as transfers (no minimum purchase requirement) and roll good form (minimum purchase of 1 roll - 15" or 30" x 30 yds).

Application Instructions

Heat Transfer Machine Settings:

Temperature: 300-305°F (140-150°C)

Pressure: 60-80 PSI or 4-6 bar (Firm)

Step 1:

Preheat garment/panel 10-20 seconds prior to application of transfer.

Step 2:

Place heat transfer onto garment/panel. Cover with kraft or teflon paper. Using heat transfer settings, apply transfer for 4-5 seconds.

Step 3:

Let garment/panel cool down to room temperature. Remove heat transfer liner warm.

Step 4:

Cover with kraft or teflon paper. Using heat transfer settings, apply transfer for 10-15 seconds for final seal.

Recommended Fabrics:

Nylon
Textured silicone coated materials
Moisture-wicking materials
Shiny polyester

Care Instructions:

Machine wash using mild detergent.
Wash temperature should not exceed 175°F (80°C)
Do not use bleach.
Dry at normal setting on household machines.
Do not commercial launder.
Do not iron directly onto heat transfer.

ALL GUIDELINES AND TECHNICAL INFORMATION ARE BASED ON WHAT WE BELIEVE TO BE ACCURATE. HOWEVER WE CANNOT GUARANTEE PERFORMANCE OF THE PRODUCT NOT UNDER THE MANUFACTURER'S CONTROL. PLEASE DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS END USE. THE USER ASSUMES ALL RISK AND LIABILITY WITH RESPECT TO THE USE OF THIS PRODUCT. WE WILL ONLY REPLACE GOODS DETERMINED BY THE SELLER AND MANUFACTURER AS DEFECTIVE.

Copyright © 2017

**Block Bindings
& Interlinings Ltd**

9500 Rue Meilleur, Suite 402
Montreal, Quebec H2N 2B7
T. (514) 381-7493
F. (514) 381-6725

